

SIMATIC ET 200SP, Analog input module, AI 2xU Standard Pack  
 quantity: 1 unit, suitable for BU type A0, A1, Color code CC00,  
 Module diagnostics, 16 bit



| General information                                       |  |
|---|--|
| Product type designation                                  | AI 2xU ST                                      |
| HW functional status                                      | from FS04                                      |
| Firmware version  |  |
| • FW update possible                                      | Yes  |
| usable BaseUnits  | BU type A0, A1                                 |
| Color code for module-specific color identification plate | CC00   |
| Product function  |  |
| • I&M data  | Yes; I&M0 to I&M3                              |
| • Isochronous mode  | No   |
| • Measuring range scalable                                | No   |
| Engineering with  |  |
| • STEP 7 TIA Portal configurable/integrated as of version | V13 SP1  |
| • STEP 7 configurable/integrated as of version            | V5.5 SP3 / -                                   |
| • PROFIBUS as of GSD version/GSD revision                 | One GSD file each, Revision 3 and 5 and higher |
| • PROFINET as of GSD version/GSD revision                 | GSDML V2.3                                     |
| Operating mode  |  |

- Oversampling No
- MSI No

### CiR – Configuration in RUN

|                                    |     |
|------------------------------------|-----|
| Reparameterization possible in RUN | Yes |
| Calibration possible in RUN        | No  |

### Supply voltage

|                                     |        |
|-------------------------------------|--------|
| Rated value (DC)                    | 24 V   |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection         | Yes    |

### Input current

|                           |       |
|---------------------------|-------|
| Current consumption, max. | 37 mA |
|---------------------------|-------|

### Encoder supply

|                                |    |
|--------------------------------|----|
| 24 V encoder supply            |    |
| • 24 V                         | No |
| Additional 24 V encoder supply |    |
| • 24 V                         | No |

### Power loss

|                  |       |
|------------------|-------|
| Power loss, typ. | 0.9 W |
|------------------|-------|

### Address area

|                                  |                                     |
|----------------------------------|-------------------------------------|
| Address space per module         |                                     |
| • Address space per module, max. | 4 byte; + 1 byte for QI information |

### Hardware configuration

|                                     |        |
|-------------------------------------|--------|
| Automatic encoding                  | Yes    |
| • Mechanical coding element         | Yes    |
| • Type of mechanical coding element | Type A |

#### Selection of BaseUnit for connection variants

- 1-wire connection BU type A0, A1
- 2-wire connection BU type A0, A1

### Analog inputs

|   |             |
|---|-------------|
| Number of analog inputs   | 2           |
| • For voltage measurement   | 2           |
| permissible input voltage for voltage input (destruction limit), max. | 30 V        |
| Cycle time (all channels), min.                                       | 500 $\mu$ s |

#### Input ranges (rated values), voltages

- 0 to +10 V Yes; 15 bit
  - Input resistance (0 to 10 V) 180 k $\Omega$
- 1 V to 5 V Yes; 15 bit

|   |   |
|---|---|
| — Input resistance (1 V to 5 V)   | 180 kΩ  |
| • -10 V to +10 V  | Yes; 16 bit incl. sign  |
| — Input resistance (-10 V to +10 V)   | 180 kΩ  |
| • -5 V to +5 V  | Yes; 16 bit incl. sign  |
| — Input resistance (-5 V to +5 V)   | 180 kΩ  |
| <b>Cable length</b>   |   |
| • shielded, max.  | 200 m   |
| <b>Analog value generation for the inputs</b>   |   |
| Measurement principle   | Sigma Delta   |
| <b>Integration and conversion time/resolution per channel</b>   |   |
| • Resolution with overrange (bit including sign), max.  | 16 bit  |
| • Integration time, parameterizable   | Yes   |
| • Interference voltage suppression for interference frequency f1 in Hz  | 16.6 / 50 / 60 Hz / off   |
| • Conversion time (per channel)   | 50 ms @ 60 Hz, 60 ms @ 50 Hz, 180 ms @ 16.6 Hz, 250 μs without filter |
| <b>Smoothing of measured values</b>   |   |
| • Number of smoothing levels  | 4   |
| • parameterizable   | Yes   |
| • Step: None  | Yes; 1x cycle time  |
| • Step: low   | Yes; 4x cycle time  |
| • Step: Medium  | Yes; 8x cycle time  |
| • Step: High  | Yes; 16x cycle time   |
| <b>Encoder</b>  |   |
| <b>Connection of signal encoders</b>  |   |
| • for voltage measurement   | Yes   |
| <b>Errors/accuracies</b>  |   |
| Linearity error (relative to input range), (+/-)  | 0.01 %  |
| Temperature error (relative to input range), (+/-)  | 0.005 %/K   |
| Crosstalk between the inputs, min.  | -50 dB  |
| Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)   | 0.05 %  |
| <b>Operational error limit in overall temperature range</b>   |   |
| • Voltage, relative to input range, (+/-)   | 0.5 %   |
| <b>Basic error limit (operational limit at 25 °C)</b>   |   |
| • Voltage, relative to input range, (+/-)   | 0.3 %   |
| <b>Interference voltage suppression for <math>f = n \times (f_1 \pm 1 \%)</math>, <math>f_1 =</math> interference frequency</b> |   |
| • Series mode interference (peak value of interference < rated value of input range), min.                                      | 70 dB   |
| • Common mode voltage, max.   | 10 V  |
| • Common mode interference, min.  | 90 dB   |

| Interrupts/diagnostics/status information                      |  |
|--|--|
| Diagnostics function   | Yes  |
| Alarms   |  |
| • Diagnostic alarm   | Yes  |
| • Limit value alarm  | No   |
| Diagnostic messages  |  |
| • Monitoring the supply voltage                                | Yes  |
| • Wire-break   | No   |
| • Short-circuit  | Yes; at 1 to 5 V   |
| • Group error  | Yes  |
| • Overflow/underflow   | Yes  |
| Diagnostics indication LED                                     |  |
| • Monitoring of the supply voltage (PWR-LED)                   | Yes; green PWR LED   |
| • Channel status display                                       | Yes; green LED   |
| • for channel diagnostics                                      | No   |
| • for module diagnostics                                       | Yes; green/red DIAG LED  |
| Potential separation   |  |
| Potential separation channels                                  |  |
| • between the channels   | No   |
| • between the channels and backplane bus                       | Yes  |
| • between the channels and the power supply of the electronics | Yes  |
| Permissible potential difference                               |  |
| between the inputs (UCM)                                       | 10 Vpp   |
| Isolation  |  |
| Isolation tested with  | 707 V DC (type test)   |
| Ambient conditions   |  |
| Ambient temperature during operation                           |  |
| • horizontal installation, min.                                | -30 °C   |
| • horizontal installation, max.                                | 60 °C  |
| • vertical installation, min.                                  | -30 °C   |
| • vertical installation, max.                                  | 50 °C  |
| Altitude during operation relating to sea level                |  |
| • Installation altitude above sea level, max.                  | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
| Dimensions   |  |
| Width  | 15 mm  |
| Height   | 73 mm  |
| Depth  | 58 mm  |
| Weights  |  |

---

Weight, approx.

31 g

**last modified:**

06/11/2020