



## Wall enclosure, +mounting plate, HxWxD=600x600x200mm

Part no. **CS-66/200**  
 Catalog No. **111698**

EL-Nummer  
 (Norway) **0002466122**

**EATON**  
 Powering Business Worldwide™

## Delivery program

Product range		Wall-mounting housing CS
Product function		Wall-mounting housing with mounting plate
Degree of Protection		IP66 IP23 (with ventilating plates)
Description		Foamed polyurethane sealing throughout. Impact resistance category IK09 to EN 62262. Sheet steel mounting plate Bottom plate with foamed gasket. Single door, door stop on the right, door opening angle 120°. Door hinge pins with quick change technology. Standardized locking system with sash fastener. Powder coating RAL 7035 inside and outside
Material		Steel plate
<b>Dimensions</b>		
Width	mm	600
Height	mm	600
Depth	mm	200
Locks	Number	2
Hinges	Number	2
Door profile molding	Number	2
Flange plates	Width x Depth mm	172 x 532
Max. F3A flanges	Number	2
<b>Mounting plates</b>		
Height	mm	570
Width	mm	550
Weight	kg	21.8
Information about equipment supplied		Lock, 3 mm double ward key Including M6 threaded welded studs for earth conductor connections in the door

## Technical data

<b>General</b>		
Standards		IEC/EN 60529, IEC 62262, IEC/EN 62208
RoHS		In accordance with Directive 2002/95/EC of the European Parliament and Council
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)		yes
Climatic proofing		Damp heat, constant, to IEC 60068-2-78; Damp heat, cyclical, to IEC 60068-2-30
Ambient temperature	°C	-40 - +70
Degree of Protection		IP66 IP23 (with ventilating plates)
Installation conditions		Indoor-/outdoor installation
Power loss		Power loss $P_v$ [W] for fully enclosed sheet steel enclosure CS without internal partitions for wall mounting. Example: max. ambient temperature 35°C; Overtemperature $\Delta T = 20$ K; Relative humidity = 75%.
Max. heat dissipation		
Individual enclosure for wall mounting	$P_v$	W 54
Starting enclosure for wall mounting	$P_v$	W 51
Middle enclosure for wall mounting	$P_v$	W 48

## Material characteristics

Material		Steel plate
Surface treatment		Structured powder spray polyester based paint finish

Surface finish		Semi-textured
Colour		light gray (RAL 7035)
Finish		Gloss
Material thickness	mm	
Body	mm	1.5
Mounting plate	mm	2
Door	mm	1.5
Bottom plate	mm	1.5

### Material properties

Mechanical			
Impact resistance			IK09 according to EN 62262
max. assembly weights			
Total of Weight of fitted components	kg	275	
Mounting plate	kg	250	
Door	kg	25	
			500 kg payload, when brackets fitted in all four enclosure corners (vertically or horizontally) and the weights are symmetrically distributed within the enclosure.

### Description/standard features

Construction		Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure.
Back plate		9 mm drilling dimensions for wall mounting
Side plates		Without apertures
Top plate		Without apertures
Bottom plate		Enclosed, foamed gasket, can be unscrewed for F3A-... flanges or for assembly by user
Mounting plate, material		Sheet steel, hot-galvanized
Door, Engineering		Including M6 threaded welded studs for earth conductor connections in the door:
Information about equipment supplied		Lock, 3 mm double ward key Including M6 threaded welded studs for earth conductor connections in the door
		<b>If electrical apparatus is to be installed in the door, a continuous, permanent protective ground contactor connection must be established with a protective ground cable. The threaded welded studs on the door and on the cabinet side wall must be used as connecting points for the ground leads.</b>
Door hinges		On the right, can be converted by user
Type Door		Door hinges right can be converted by user
door opening angle		120°
Door interlock		Protection insulated turn-buckle Standard closure 3 mm double-ward key
Locks	Number	2

### Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure for wall mounting	P <sub>v</sub>	W	55
Starting enclosure for wall mounting	P <sub>v</sub>	W	52
Middle enclosure for wall mounting	P <sub>v</sub>	W	49
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure for wall mounting	P <sub>v</sub>	W	110
Starting enclosure for wall mounting	P <sub>v</sub>	W	104
Middle enclosure for wall mounting	P <sub>v</sub>	W	99
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			Meets the product standard's requirements.
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply to enclosures without lifting aids.
10.2.6 Mechanical impact	IK09
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES	IP66_x
10.4 Clearances and creepage distances	Is the panel builder's responsibility.
10.5 Protection against electric shock	< 0.1 Ω; meets the product standard's requirements.
10.6 Incorporation of switching devices and components	Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9 Insulation properties	
10.9.2 Power-frequency electric strength	U <sub>i</sub> = 1000 V AC
10.9.3 Impulse withstand voltage	Does not apply to basic enclosures as defined in EN 62208.
10.9.4 Testing of enclosures made of insulating material	Does not apply to metal enclosures.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility.
10.13 Mechanical function	Meets the product standard's requirements.

## Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Enclosure/switchgear cabinet (empty) (EC000261)

Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet (ecl@ss10.0.1-27-18-01-01 [AGZ056016])

Width	mm	600
Height	mm	600
Depth	mm	200
Material		Steel
Material quality		Other
Surface finishing		Powder coating
Colour		Grey
RAL-number		7035
With mounting plate		Yes
Mounting plate depth-adjustable		Yes
Number of locks		2
Floor installation possible		Yes
Wall fastening possible		Yes
Wall build in		Yes
Pole fastening		Yes
Tackable		Yes
Number of doors		1
Suitable for metrical mounting		Yes
Suitable for outdoor set-up		No
Pitched roof		No
EMC-version		Yes
With glazed door		No
With ventilation door		No
With backside door		No
Impact strength		IK09
Degree of protection (IP)		IP66
Degree of protection (NEMA)		12

## Approvals

Product Standards	UL 508A; CSA-C22.2 No.14; IEC/EN 60529; CE marking
UL File No.	E336299
UL Category Control No.	NITW

CSA File No.	–
CSA Class No.	–
North America Certification	Request filed for CSA
Conditions of Acceptability	Series CS may be provided with metal sub-panel. No back mounted components are allowed between sub-panel and the back sheet metal enclosure
Specially designed for North America	No
Suitable for	Industrial Control Panels
Degree of Protection	IEC: IP66, indoor and outdoor; UL/CSA Types 1, 12, indoor only.

## Dimensions

Dimensions

## Additional product information (links)

### AWA4300-2521 CS wall-mounted sheet steel enclosures with mounting plate

AWA4300-2521 CS wall-mounted sheet steel enclosures with mounting plate [ftp://ftp.moeller.net/DOCUMENTATION/AWA\\_INSTRUCTIONS/25210414.pdf](ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/25210414.pdf)

Declaration of conformity [http://intranet.moeller.net/technik\\_daten/file/produkt\\_deklarationen/file/konformitaeten/00002/00002259.pdf](http://intranet.moeller.net/technik_daten/file/produkt_deklarationen/file/konformitaeten/00002/00002259.pdf)